

# HT-IPA

## Flammable Solvent Cleaning Systems

Model	Capacity	Tank Dimensions	Unit Dimensions	Ultrasonic Power
HT-1306-IPA	3	13" x 6" x 10" (8"LL)	43" x 27" x 24"	280w
HT-2011-IPA	11	20" x 11" x 14" (12"LL)	43" x 27" x 24"	840w

### Standard Features:

- All stainless steel construction
- 14 gauge 316L stainless steel tank, 304 stainless steel skirt
- High intensity 40kHz ultrasonics
- Powered by Neptune™ 40 kHz generator with sweep frequency
- Piezoelectric, metallurgically bonded transducers
- Thermostatically controlled heat
- 120 V, 1Ø, 60 Hz power, filtered, regulated compressed air - 25 p.s.i. @ 70 .f.m., cooling water - 0.5 g.p.m.
- Over-temperature protection
- Fusible link safety cover
- Low purge pressure interlock
- Purge pressure delay-on
- Ultrasonic 30 minute timer
- Ultrasonic cycle start
- Purge system OK annunciator
- Low purge pressure annunciator
- Over temperature annunciator



ETL LISTED  
**CONFORMS TO  
 ANSI/UL STD 73  
 CERTIFIED TO  
 CAN/CSA C22.2 STD NO. 68**

**Equipment has been approved for "Class I, Division I Group D, T3" locations when properly installed according to the National Electric Code**

Front View



Side View



# BLACKSTONE~NEY

## ULTRASONICS

**Contact:** Certech  
 Steve Bahr  
 sales.certech@gmail.com  
 (408) 263-6835

Division of Cleaning Technologies Group, LLC.  
 Phone: (716) 665-2340  
 Fax: (716) 665-2480  
 Web Site: www.blackstone-ney.com

A NM Group Global, LLC Company